



An ISO 9001
Company

Bharat Heavy Electricals Limited

(High Pressure Boiler Plant)

Tiruchirapalli – 620014, TAMIL NADU, INDIA

MATERIALS MANAGEMENT / CAPITAL EQUIPMENT

ENQUIRY NOTICE INVITING TENDER	Phone: +91 431 257 7653 Fax : +91 431 252 0031 Email : skaruna@bheltry.co.in , Web : www.bhel.com
---	---

TWO PART BID Tender to be submitted in Two Parts	Enquiry Number: 2731300011	Enquiry Date: dt.28.05.2013	Due date for submission of quotation dt.28.06.2013
---	--------------------------------------	---------------------------------------	--

You are requested to quote the Enquiry number date and due date in all your correspondences. This is only a request for quotation and not an order.

Please note that under any circumstances both delayed offer and late offers will not be considered. Hence vendors are requested to ensure that the offer is reaching physically our office before 14.00 Hrs on the date of tender opening

Item No.	Item Description	Quantity
	Supply, Erection and Commissioning of Variable Speed Self Centering Rotators of the following capacities as per the Technical Specification & Commercial Conditions applicable (to be downloaded from web site www.bhel.com or http://tenders.gov.in)	
10	Variable Speed Self Centering Rotators 10 Ton	01 Set
20	Variable Speed Self Centering Rotators 25 Ton	01 Set
30	Variable Speed Self Centering Rotators 50 Ton	01 Set

Important Points to be taken care during the submission of offer:-

1. Bidder's Response Column in technical specification sheet to be duly filled in without fail. Additional details provided in the offer may be supported with documentary evidence.
2. Check list to be filled and enclosed along with the offer failing which, the offer will not be considered for evaluation.
3. The equipment shall be guaranteed for 18 months from the date of supply or 12 months from the date of commissioning whichever is earlier.

BHEL's General guidelines /instructions including bank guarantee formats and list of consortium banks, commercial terms checklist can be downloaded from BHEL web site <http://www.bhel.com> or from the government tender website <http://tenders.gov.in> (public sector units > Bharat Heavy Electricals Limited page) Tender Enquiry reference "2731300011"

Tenders should reach us before 14:00 hours on the due date Tenders will be opened at 14:30 hours on the due date Tenders would be opened in presence of the tenderers who have submitted their offers and who may like to be present	Yours faithfully, For BHARAT HEAVY ELECTRICALS LIMITED Engineer / MM / Capital Equipment
--	---

Part A: COE :TI:ATP:

PART A**QUALIFYING CRITERIA FOR THE SUPPLY OF“ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS” AS PER PART-B OF TECHNICAL SPECIFICATION.****SECTION – I**

The BIDDER is expected to give complete details against each clause in the table given below, with additional sheets those may be attached (giving clear reference number) to furnish and cover the requisite details / documents.

S. No.	PARTICULARS	BIDDER'S RESPONSE
1	BIDDER to provide the Profile of their Company	
2	The Bidder (OEM) shall have a minimum of TEN Years of Continuous Experience in the field of Design, Manufacture and Supply of“ <u>ELECTRONICALLY CONTROLLED VARIABLE SPEED <u>SELF CENTERING</u> JOB ROTATORS</u> ”.	
3	List of customers to whom “ <u>ELECTRONICALLY CONTROLLED VARIABLE SPEED <u>SELF CENTERING</u> JOB ROTATORS</u> ”weresupplied, installed and commissioned till date.	
4	Details on SERVICE-AFTER-SALES Set-Up in India including the Addresses of Agents / Service Centres in India.	
5	Any Additional Data to supplement the manufacturing capability of the BIDDER for the subject equipment.	

Part A: COE :TI:ATP:

SECTION – II

The BIDDER has to compulsorily meet the following requirements to get qualified for submitting an offer for the “**ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS**”

S. No.	REQUIREMENTS	BIDDER'S RESPONSE
1	Only those Bidders (OEMs) should quote, who have supplied and commissioned at least TEN SETS OF“ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS” , of capacity 50,000 kg or higher, in the past three years (on the date of opening of Tender) and such machine should presently be working satisfactorily for more than one year after commissioning (on the date of opening of Tender),.	
	The Bidder should submit following information where the “ ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS ”have been supplied:	
1.1	Name and postal address of the customer or company where similar equipment is installed.	
1.2	Name and designation of the contact person of the customer.	
1.3	Phone, FAX no and email address of the contact person of the customer.	
1.4	Month and Year of commissioning of the equipment.	
1.5	Application for which the equipment is supplied	
2	Along with the Technical offer, the Bidder should submit the <u>Performance certificates from the customers</u> for the satisfactory performance of the equipment supplied as per clause 1.0 above. (For obtaining the Performance certificate, a suggestive format is provided in SECTION – IV)	
3	Offers of only those Bidders who meet the above Qualifying Criteria will be considered for further evaluation.	
4	BHEL reserves the right to verify the information provided by Bidder. In case the information provided by Bidder is found to be false/ incorrect, the offer shall be rejected.	

Part A: COE :TI:ATP:

SECTION – III

The BIDDER has to comply with the following, for accepting the Technical Offer for scrutiny by the Purchaser:

S.No	REQUIREMENTS	BIDDER's COMPLIANCE
1	The BIDDER shall submit the offer in TWO PARTS-Technical [with PART A & PART B] & Commercial and Price Bid.	
2	The offer shall contain a comparative statement of Technical Specifications given by BHEL and the offered details submitted by the Bidder, against each clause. Merely stating 'CONFIRMED' or 'COMPLIES' or 'YES' or 'NO-DEVIATION' or similar words wherever 'Bidder to Specify' details in the technical comparative statement may lead to disqualification of the Technical Offer.	
3	The Technical Offer shall be supported by product Catalogues & Data Sheets and also technical details of Bought-Out-Items with copies of Product Catalogue to the extent possible.	
4	The Commercial Offer (given with the Technical Offer) shall contain the Scope of Supply and the Un-Priced Part of the Price-Bid, for confirmation of the inclusion of all the accessories, tooling's, attachments, auxiliary parts, spares, consumables, etc. with the main and basic equipment, to meet the technical specification requirements.	
5	BIDDER has to indicate the Country of Origin for the supply of equipment.	

Part A: COE :TI:ATP:

SECTION – IV

PERFORMANCE CERTIFICATE
(On Customer's Letter Head)

1. Supplier of the “**ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS**” :

2. Make & Model of the “**ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS**” :

3. Month & Year of Commissioning :

4. Application for which the “**ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS**”is used:

5. Size & weight carrying capacity of the “**ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS**”

6. Performance of the equipment : Satisfactory / Good / Average /
(Strike off whichever is not applicable) Not Satisfactory

7. After Sales Service : Satisfactory /Good /Average /
Not Satisfactory

8. Any other remarks :

Date:

Signature & Seal of the Authority
issuing the Performance Certificate

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
1.0	<u>APPLICATION:</u> a. For use in heavy fabrication of Pressure Vessels and Heat Exchangers which are cylindrical in shape and welded with attachments and nozzles.	Vendor to note	
2.0	<u>Scope of Supply:Supply, Erection and Commissioning of</u> A. 10 T capacity Electronically controlled Variable Speed Self Centering Rotators – 1 Set B. 25 T capacity Electronically controlled Variable Speed Self Centering Rotators – 1 Set C. 50 T capacity Electronically controlled Variable Speed Self Centering Rotators – 1 Set (The Rotator has to be supplied in “ Pair ”consisting of <u>One Drive Unit and One Idler Unit</u> , in combination to able to make butt joints of long shells and alsoshould able to rotate the job in either direction) <u>which includes:</u> a. Detailed Design, Manufacture and supply as per BHEL specifications b. Assembly and Testing before Dispatch c. Supply of Electric & Mechanical Spares d. Erection (Assembly), Commissioning and Performance Prove-Out at BHEL e. Training on Maintenance for BHEL personnel f. Performance Guarantee for 12 months, from the date of commissioning g. O & M Manuals and related documents	Vendor to Confirm	
3.0	TECHNICAL SPECIFICATIONS		
3.1.0	ROTATOR DRIVE UNIT:		
3.1.1	Weight Carrying Capacity : A. 7.50 Metric Tons (minimum capacity for design) B. 18.25Metric Tons (minimum capacity for design) C. 37.50 Metric Tons (minimum capacity for design)	Vendor to Confirm	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
3.1.2	Rotating Capacity : A. 10 Metric Tons B. 25 Metric Tons C. 50 Metric Tons	Vendor to Confirm	
3.1.3	Eccentric Loading: 20 % of the Job Weight	Vendor to Confirm	
3.1.4	Wheel Surface Speed : 60 mm to 1200 mm / minute (approx.), with step less speed variation	Vendor to Confirm	
3.1.5	Wheel Drive Mechanism: Electronically Controlled Drive System giving mechanical drives through electric motor.	Vendor to Confirm	
3.1.6	Electric Motor & Drive: AC Motor with suitable Variable Speed Drive, to take care of eccentric loading and uniform job rotation in either direction. The induction motor shall be suitable for VFD application.All the electrical components like motor, etc. shall be properly earthed.	Vendor to Confirm& provide motor & VFD details (like make, model)	
3.1.7	Rotator Operation: Shall be controllable either from Main control panel or from the hand held remote pendant. A Key type selector switch has to be provided for Local / Remote selection at Main control panel.	Vendor to Confirm	
3.1.8	A hand held remote unit with the following features has to be provided: (a) Remote ON / OFF selector switch (b) Single turn Potentiometer for speed variation (c) Emergency Off Push button (d) 2 way selector switch for rotator forward / reverse operation The remote cable shall be connected to the Main control panel through easily detachable Plug & sockets and length of the connecting cable shall be 15 mtrs. The cable shall be routed through a metallic braided hose and suitable provision shall be provided on the rotator to wind and keep the remote cable safely when the remote is not in use.	Vendor to Confirm& to provide the layout / sketches	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
3.1.9	The control cables & power cables shall be routed through metallic cable tray / flexible conduit and they shall be properly clamped on the positioner.	Vendor to confirm	
3.1.10	Electro - Mechanical Drive Details: BIDDER to give details on the mode of power transmission from the electric motor to the gear-box driving the rotator wheel along with offer.	Vendor to provide details	
3.1.11	Gear Box Details: BIDDER to furnish complete technical details of the Gear Box used for mechanical power transmission. BHEL prefers vendor to use standard gear boxes rather than built in gear boxes. Planetary Gears not permitted.	Vendor to provide details	
3.2.0	ROTATOR IDLER UNIT:		
3.2.1	Weight Carrying Capacity : A. 7.50 Metric Tons (minimum capacity for design) B. 18.25Metric Tons (minimum capacity for design) C. 37.50 Metric Tons (minimum capacity for design)	Vendor to confirm & provide details	
3.2.2	Eccentric Loading : 20 % of the Job Weight	Vendor to Confirm	
3.2.3	Welding return cable connection on the positioner: Suitable arrangement to be provided on the idler unit for connecting the welding return cables and to ensure the proper conductivity of welding current through job, rotator wheels to the welding machine. The maximum welding current to be carried is 1200A.	Vendor to confirm & provide details	
4.0	GENERAL FEATURES / INPUTS for DESIGN & FABRICATION of both the DRIVE & IDLER UNITS:		
4.1	Outer Diameter Range of Job (approx.): A. 400 to 4000 mm B. 400 to 4000 mm C. 500 to 5000 mm	Vendor to confirm & provide details	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
4.2	Size of Wheel (Diameter X Width -approx.): A. 400 X 90 mm B. 400 X 140 mm C. 500 X 140 mm	Vendor to confirm & provide details	
4.3	Wheel Material : Solid Steel Forging	Vendor to confirm	
4.6	Wheel Contact Surface Hardness : 300-350 BHN	Vendor to confirm	
4.7	Wheel Surface Profile : Crowning Surface	Vendor to confirm	
4.8	Wheel Adjustment : Each wheel assembly with Housing/Bracket and Integral Drive Unit shall be movable on the Rotator Base Frame, through a manually driven screw-rod in Drive Unit and Idler Unit. It shall be possible to locate and lock each wheel assembly on the Rotator Base Frame at required pitches to cover the job diameter range. The drive arrangement to be designed to avoid loading on the screw-rod while loading / after loading the job on the wheels.	Vendor to confirm & provide details	
4.9	Hardness and finish of Base frame slide: The sliding surfaces of the base frame in Drive and idler units shall be hardened and machined.	Vendor to confirm	
4.10	Wheel Alignment: The alignment of the wheel face in the plane perpendicular to the wheel shaft axis to be maintained within 1mm for the entire stroke of the wheel assembly positions on the base frame.	Vendor to confirm	
4.11	Wheel Positioning: There shall be suitable provision for locking the wheel assembly with the base frame, to prevent movement of wheel assembly under working/loaded conditions.	Vendor to confirm & provide details	
4.12	Wheel Shaft Assembly: The high grade shafts are to be shrunk fit into wheel assemblies / with shrink disc, to eliminate the provision of key arrangement	Vendor to confirm	
4.13	Wheel Support: Wheels are to be supported on Heavy Duty Roller Bearings	Vendor to confirm	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
4.14	Lifting Hook: Four numbers of Lifting Hook are to be provided at suitable locations for facilitating lifting the entire rotator unit by EOT Crane in a geometrically balanced state.	Vendor to confirm	
4.15	Cover for Gears: Suitably profiled steel outer-covers (with easily replaceable provisions) are to be provided for the spur gears, to protect from welding flux, slag and other foreign particles, while in operation. The thickness of the cover plate shall be minimum 3mm.	Vendor to confirm	
4.16	Cover for base frame: Suitably profiled steel covers (with easily replaceable provisions) are to be provided to cover the sliding surface (top face) of the base frame, to protect from welding flux, slag and other foreign particles falling on it, while in operation. The thickness of the cover plate shall be minimum 3mm.	Vendor to confirm	
4.17	Job Temperature: The ROTATORS will be used in the Fabrication Shop floors, where the jobs are pre-heated / post-heated to a temperature of maximum 300 °C and hence the mechanical parts coming in contact with the jobs are to be designed to withstand this high temperature.	Vendor to confirm	
4.18	Electric Power Input: A 3 phase, 415 ± 10% V, 50 ± 2% Hz AC input supply will be provided at machine terminals.	Vendor to confirm	
4.19	The Main Control Panel shall have the following features: (a) A suitable capacity MCB as Main switch for On/ Off. The MCB shall be operable without opening the control panel door. (b) Indication lamp for the indication of Main On / Power On, Drive Trip. (c) Emergency Stop Push button. (d) 2 - way selector switch for rotator Forward / Reverse selection (e) A single turn POT for setting the RPM. (f) Key type Local / Remote selector switch. (g) Sufficient capacity Cooling fan with required Air filter. All the electrical components shall be of 'DIN rail' mountable type and the panel shall have IP 54 protection.	Vendor to confirm	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
4.20	Ambient Condition: Indoor Working Environment with temperature up to 50 ° C and Humidity up to 85%, but both not occur simultaneously. Hence, the offered equipment shall be of tropicalised in design.	Vendor to confirm	
4.20	Control Voltage : The control Voltage shall be 24 V AC / DC.	Vendor to confirm	
5.0	<u>Bought-Out Items:</u> a. BIDDER has to list down all the Bought- Out Items and their makes / brand names with technical specifications. b. Bought-Out Items / Components supplied make shall be ABB / SIEMENS / GE / BALDOR / KIRLOSKAR for Electric Motors and TIMKEN / FAG / SKF for Bearings. c. The variable speed drive shall be of ABB / SIEMENS / ALLEN BRADLEY / L&T / Danfoss / AMTECH make. d. The Gear boxes shall be of Greaves / Elecon / Bonfiglioli.	Vendor to confirm & provide details	
7.0	STRUCTURAL FABRICATION :		
7.1	Rotator Base Frame and Heavy Wheel Bracket / Housing: Steel Fabrication Procedures to be followed. The Base Frame work shall be with steel plates of sufficient thickness, including REINFORCING RIBS.	Vendor to confirm & provide details	
7.2	Raw Material: Only steel plates tested and certified for quality by reputed inspection authorities, shall be used. Test Certificates to be produced for BHEL verification and form part of the documentation.	Vendor to confirm	
7.3	Welded Joints: No Butt Joints are allowed for Plate Build-Up to increase effective length	Vendor to confirm	
7.4	Welding Electrodes: For all Welding E 7018 Electrode/higher grade shall be used.	Vendor to confirm	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
7.5	Welded Joint Testing: All Fillet Welded Joints shall be subjected to Non Destructive Testing like Liquid Penetrant Test (LPI) and Magnetic Particle Inspection (MPI). Testing Documents to be produced for BHEL evaluation and form part of the documentation. Random MPI / LPI to be shown to BHEL inspectors at the time of inspection at vendor's works.	Vendor to confirm	
7.6	Heat Treatment & NDT Examination: The Structural Items (Base Frame / Wheel Housing, etc.) shall be Stress Relieved by thermal heat-treatment process after welding and NDT examinations. All welding shall be tested by NDT means [MPI or LPI] after Stress Relieving operation.	Vendor to confirm	
7.7	Machining Operation: All mechanical mating sliding surfaces are to be machined and ground to the required finish after heat treatment and protected.	Vendor to confirm	
7.8	Surface Cleaning: All steel parts are to be shot blasted or chemically treated for surface cleaning, after completion of all operations but prior to painting.	Vendor to confirm	
7.9	<p>Painting:The ROTATORS are to be painted as follows :</p> <ol style="list-style-type: none"> One coat of Primer (Zinc Chromate) with 25 μ of DFT (Dry Film Thickness) and 48 hours of compulsory curing after painting. Two coats of Enamel Paint [Ethyl Zinc Silicate of Colour Apple Green] each with a DFT of 25 μ and intermittent curing of 16 hours. RotatingCapacity in Metric Ton shall be painted legibly in each unit. 	Vendor to confirm	
7.10	Frame Dimensions: BIDDER has to indicate the tentative DIMENSIONS for the Base Frame of Drive and Idler Units and Wheel Brackets	Vendor to provide details	
8.0	<p>SPARES SUPPLY: BIDDER to Quote for the following spares along with the rotator for two years of trouble free operation:</p> <ol style="list-style-type: none"> Bearings for each wheel assembly Seals, gaskets & Belts used in the Rotator Pulleys & Couplings used in the Rotator Variable Frequency Drive for each capacity rotator 	Vendor to provide a separate unpriced complete list of spares	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
8.1	<p>The following Electrical maintenance tools kit& instrument – 2 Nos. for each capacity rotator has to be supplied:</p> <p>(a) Electrical maintenance Tool kit (DAYTON make, 41 pcs, 3 way screwdriver bit socket set, DAYTON model no: SD-192-HS)</p> <p>(b) MECO make digital Multimeter, Model: 801 Auto)</p>	Vendor to confirm	
9.0	DRAWINGS / DOCUMENTS / DETAILS:		
9.1	<p><u>Drawings and Documentsafter receipt of P.O.:</u> The following documents and details are to be submitted for BHEL Approval, with in one month after the receipt of PO - prior to taking up the manufacture of the ROTATORS:</p> <ol style="list-style-type: none"> a. GA Drawing of the ROTATOR. b. GA Drawing of Wheel Drive Mechanism. c. GA drawing of wheel shifting mechanism in Drive & Idler Units. d. GA Drawing of Electric/Electronic System. e. Sub-Assembly Drawing for Wheels. f. Calculations for Selection of Electric Motors, Gear Reducers, etc. g. Wiring Diagram with Logic Circuits. h. Weight of the ROTATOR (Drive Unit & Idler Unit separately) including all Electrical Equipment. <p>Note: All the drawings should have the major & critical dimensions and list of bought out items with make and specification.</p>	Vendor to confirm	

SPECIFICATION FORELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFERWith
9.2	<p><u>Drawings and Documentsalong with Equipmentsupply:Drawings and Documentsalong with Equipmentsupply:</u>Warranty Card for all Bought-Out Items</p> <ol style="list-style-type: none"> a. Trouble Shooting Chart for all Sub-Systems b. Electrical circuit diagram of the panel c. VFD drive Programming / User manual d. VFD drive Parameter manual e. Mechanical manufacturing drawings for all wearing components. f. Operation & Maintenance manual with complete specification of the equipment and Preventive Maintenance check list. 		
9.2 Contd..	<p>Note:</p> <ol style="list-style-type: none"> 1. One soft copy of the entire documents stated above to be provided in Pen drive. 2. One Hard copy and one soft copy to be submitted at the time of inspection at suppliers works for checking the sufficiency of the documents. If any additional requirements are found needed for maintenance, it should be provided. 	Vendor to confirm	
10.0	<p><u>Inspection :</u> The following Schedule of Inspection is to be carried out, prior to dispatch from the Supplier's Works :</p> <ol style="list-style-type: none"> a. Verification of Test Certificate for Raw Materials & Bought-Out Items used. b. Random Testing on the Welds, by physical examination and NDT c. Wheel alignment as per clause 6.10. d. Idle Run Test and Test under simulated conditions (on mutually agreed e. Verification of O&M Manuals as per clause 9.3. 	Vendor to confirm	
11.0	ROTATOR ERECTION & COMMISSIONING		

SPECIFICATION FOR ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFER With
11.1	Erection / Assembly: Erection / Assembly of the ROTATORS will have to be done by the Qualified Technical Representative of the Supplier at BHEL Works	Vendor to confirm	
11.2	Commissioning: Commissioning of the ROTATOR and Performance Prove – Out for Carrying & Rotating Capacity and Smooth Functioning of the ROTATOR (at BHEL Works) shall be the RESPONSIBILITY of the supplier.	Vendor to confirm	
11.3	The supplier shall arrange training for two BHEL engineers at VFD drive manufacturer's works in India for a period of not less than two days on drive programming, troubleshooting and maintenance. The boarding & lodging charges of BHEL personal will be borne by BHEL.	Vendor to confirm	
12.0	PERFORMANCE GUARANTEE : The Performance of the ROTATOR in Total and / or the Components / Sub Assemblies / Bought-Out-Items shall be guaranteed for a period of 12 Months from the date of performance acceptance at BHEL Works or 18 Months from the date of supply whichever is earlier.	Vendor to confirm	
13.0	CHECK LIST:		

SPECIFICATION FOR ELECTRONICALLY CONTROLLED VARIABLE SPEED SELF CENTERING JOB ROTATORS

Part B

Clause	PARTICULARS AND BHEL SPECIFICATION		BIDDERS OFFER With
13.1	<p>The following documents and details are to be submitted along with the Offer for Technical evaluation:</p> <ul style="list-style-type: none"> a. GA Drawing of the ROTATOR. b. GA Drawing of Wheel Drive Mechanism c. GA Drawing of Electric/Electronic System. d. Sub-Assembly Drawing for Wheels. e. Calculations for Selection of Electric Motors, Gear Reducers, etc. f. Weight of the ROTATOR (Drive Unit & Idler Unit separately) including all Electrical Equipment. g. Documents mentioned in <u>PART-A</u> including valid Performance Certificate <p>Note: All the drawings should have the major & critical dimensions and list of bought out items with make and specification.</p>	Vendor to provide.	