

PSGSG /12- 13/03	Product Specifications For ALUMINIUM Pipe		Drg. No.									
			Date	29.02.2016								
			Product	CGSM 145								
1.0	Application: Aluminum pipe shall be used for Gas Insulated switchgear Equipment.											
2.0	Material: HE -30 Aluminum Pipe/Bush											
3.0	Dimensions:											
	<table border="1"> <thead> <tr> <th>S.No</th> <th>Diameter(mm)</th> <th>Length/Thic kness(mm)</th> <th>Qty.</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>OD=330±0.5, ID=190±0.5</td> <td>445±0.5</td> <td>10</td> </tr> </tbody> </table>				S.No	Diameter(mm)	Length/Thic kness(mm)	Qty.	1	OD=330±0.5, ID=190±0.5	445±0.5	10
S.No	Diameter(mm)	Length/Thic kness(mm)	Qty.									
1	OD=330±0.5, ID=190±0.5	445±0.5	10									
4.0	Specifications:											
	<ol style="list-style-type: none"> Electrical conductivity of material shall be greater than 45%. (IACS) Surface finish of the components shall be at least RA 0.8. The component shall be free from dirt, grease and loose particles. Warranty shall be given for 12 months from the date of acceptance. Raw materials test certificate shall be submitted before dispatch. Materials shall be delivered within 45 days from the date of issue of P.O. 											
1/1	PSGSG/12-13/03.doc			Signature								