

ANNEXURE - C to BAP/CAPITAL/2012-13/OT-15

TELEPHONE CABLE TECHNICAL SPECIFICATIONS

S.No	DESCRIPTION	UNIT	QUANTITY	LOT SIZE	QUOTED / " YES or NO"
1	100 pair 0.63 mm dia Armoured Jelly filled Telephone cable annealed bare copper conductor, solid polyethylene insulated and sheathed as per technical specification GR/CUG-01/03 August- 2003	MR	4500	3 (Each 1500MR)	
2	20 pair 0.63 mm Jelly filled Armoured Telephone cable annealed bare copper conductor, solid polyethylene insulated and sheathed as per technical specification GR/CUG-01/03 August-2003	MR	1000	1	
3	10 pair 0.63 mm Jelly filled Armoured Telephone cable annealed bare copper conductor, solid polyethylene insulated and sheathed as per technical specification GR/CUG-01/03 August- 2003	MR	1000	1	
4	5 pair 0.63 mm PVC insulated Unarmoured Telephone cable as per Technical specification of GR/WIR 06/03 March-2002	MR	1000	1	
5	2 pair 0.63 mm PVC insulated Unarmoured Telephone cable as per Technical specification of GR/WIR 06/03 March-2002	MR	1000	1	
6	Single pair 0.63 mm PVC insulated Telephone cable drop wire as per TEC Specification no. GR/WIR-06/03 March-2002	MR	1000	1	