



**BHARAT HEAVY ELECTRICALS LIMITED  
CENTRALISED STAMPING UNIT  
& FABRICATION PLANT  
Jagdishpur**

**TENDER FOR CONSTRUCTION OF MULTI-STOREY  
FLATS OF TYPE-A,B,C,D & CEO RESIDENCE & OTHER  
UTILITY BUILDINGS, SERVICES ETC INCLUDING  
FINISHING WORKS FOR TOWNSHIP AT JAGDISHPUR.**

**Tender Enquiry No: BHE/FP/CVL/ 021**

**Corrigendum - I**

**BHARAT HEAVY ELECTRICALS LIMITED  
(A GOVERNMENT OF INDIA UNDERTAKING)  
CSU & FP  
Industrial Area  
Jagdishpur (UP) 227817**

Following changes may be noted:

**Section II - GENERAL CONDITIONS OF CONTRACT(GCC)**

| <b>DESCRIPTION AS PER REF.</b>                                    | <b>DESCRIPTION AS PER REF. TO BE READ AS</b>                                |
|---|---|
| <b>35.0 CONTRACTOR'S SITE OFFICE</b>                              | <b>36.0 CONTRACTOR'S SITE OFFICE/<br/>SUPERVISION</b>                       |
| <b><u>Clause 35.1</u> under the head CONTRACTOR'S SITE OFFICE</b> | <b><u>Clause 36.1</u></b>   |
| <b>36.0 CONTRACTOR'S SUPERVISION</b>                              | <b><u>This head is already merged with<br/>CONTRACTOR'S SITE OFFICE</u></b> |
| <b><u>Clause 36.1</u></b>   | <b><u>Clause 36.2</u></b>   |
| <b><u>Clause 36.2</u></b>   | <b><u>Clause 36.3</u></b>   |
| <b><u>Clause 36.3</u></b>   | <b><u>Clause 36.4</u></b>   |
| <b><u>Clause 36.4</u></b>   | <b><u>Clause 36.5</u></b>   |
| <b><u>Clause 36.5</u></b>   | <b><u>Clause 36.6</u></b>   |
| <b><u>Clause 36.6</u></b>   | <b><u>Clause 36.7</u></b>   |
| <b><u>Clause 36.7</u></b>   | <b><u>Clause 36.8</u></b>   |
| <b><u>Clause 36.8</u></b>   | <b><u>Clause 36.9</u></b>   |

**Section III - SPECIAL CONDITIONS OF CONTRACT (SCC)**

| <b>DESCRIPTION AS PER REF.</b>  | <b>DESCRIPTION AS PER REF. TO BE READ AS</b>   |
|---|--|
| <b><u>Annexure- SCC III</u><br/>INDICATIVE LIST OF INSPECTION MEASURING AND TESTING EQUIPMENTS (IMTEs) TO BE ARRANGED BY THE CONTRACTOR AT HIS OWN COST</b> | <b><u>Annexure- SCC II</u><br/>INDICATIVE LIST OF INSPECTION MEASURING AND TESTING EQUIPMENTS (IMTEs) TO BE ARRANGED BY THE CONTRACTOR AT HIS OWN COST</b> |

**Section IV - BILL OF QUANTITIES (BOQ) AND PRICE SCHEDULE**

| <b>Item No.</b> | <b>DESCRIPTION AS PER REF.</b>   | <b>DESCRIPTION AS PER REF. TO BE READ AS</b>   |
|-----------------|--|--|
| 18.             | Brick Coba Waterproofing treatment   | 1 <sup>st</sup> course to be read as 1 <sup>st</sup> course<br>2 <sup>nd</sup> course to be read as 2 <sup>nd</sup> course<br>4 <sup>th</sup> course to be read as 3 <sup>rd</sup> course<br>5 <sup>th</sup> course to be read as 4 <sup>th</sup> course<br>3 <sup>rd</sup> course to be read as 5 <sup>th</sup> course  |
| 48.             | Supply and fixing grade IV wall tiles tiles 300x400 mm with glazed finish of Kajaria/ Jhonson/ Somany etc conforming to IS: 15622 (thickness to be specified by manufacturer) of approved make in all colours, shades with <u>handmade boarders</u> skirting or dado laid with cement mortar 1:3 (1 cement : 3 course sand) and jointing with grey cement slurry @ 3.3 Kg per Sqm incl. pointing in white cement with pigment of matching shade complete finished with white cement slurry jointing and polishing complete including supply of all materials, labour and T&P etc. as per approved by engineer. | Supply and fixing grade IV wall <u>tiles</u> 300x400 mm with glazed finish of Kajaria/ Jhonson/ Somany etc conforming to IS: 15622 (thickness to be specified by manufacturer) of approved make in all colours, shades with <u>handmade, factory finished boarders</u> (3" high with <u>matching shade &amp; finish</u> ) skirting or dado laid with cement mortar 1:3 (1 cement : 3 course sand) and jointing with grey cement slurry @ 3.3 Kg per Sqm incl. pointing in white cement with pigment of matching shade complete finished with white cement slurry jointing and polishing complete including supply of all materials, labour and T&P etc. as per approved by engineer. |
| 49.             | Supply and fixing 300mm x 400 mm Jointless wall tiles (thickness to be specified by manufacturer) with <u>handmade boarders</u> of approved make (Somany or equivalent) in all colours, shades in skirting or dado as per manufacturers specifications laid with 1:3 cement and approved coarse sand mortar finished with white cement slurry jointing and polishing complete including supply of all materials, labour and T&P etc. as per approved by engineer.  | Supply and fixing 300mm x 400 mm Jointless wall tiles (thickness to be specified by manufacturer) with <u>handmade, factory finished boarders</u> (3" high with <u>matching shade &amp; finish</u> ) of approved make (Somany or equivalent) in all colours, shades in skirting or dado as per manufacturers specifications laid with 1:3 cement and approved coarse sand mortar finished with white cement slurry jointing and polishing complete including supply of all materials, labour and T&P etc. as per approved by engineer.   |
| 54.             | Melamine Polishing   | The unit of this item shall be Sqm.  |
| 58.             | Enamel Paint   | The unit of this item shall be Sqm.  |
| 60.             | P.O.P. Cornice   | Size of the cornice is 3"x 3".   |
|                 |  |  |

| Item No. | DESCRIPTION AS PER REF.   | DESCRIPTION AS PER REF. TO BE READ AS  |
|----------|---|--|
| 127.     | Providing and fixing buffed/ polished and lacquered stainless steel (SS) railing as per drawing made of <u>vertical balusters</u> of 37.5mm dia. heavy gauge pipe with 37.5mmx 37.5 mm x 6 mm "U" shaped lacquered stainless steel section/ brackets to hold the railing including providing three strands of SS rods of 12 mm bar equally spaced including lacquered stainless steel bolts etc fitted to bellustrude along with suitable toe guard. Hand rail to be 50mm medium gauge lacquered stainless steel pipe balustrade fitted with 6 mm thick stainless steel flats and stainless steel shoes as approved by engineer and securely fixed to RCC work. | Providing and fixing buffed/ polished and lacquered stainless steel (SS) railing as per drawing made of <u>vertical balusters @ 1 m c/c</u> of 37.5mm dia. heavy gauge pipe with 37.5mmx 37.5 mm x 6 mm "U" shaped lacquered stainless steel section/ brackets to hold the railing including providing three strands of SS rods of 12 mm bar equally spaced including lacquered stainless steel bolts etc fitted to balustrade along with suitable toe guard. Hand rail to be 50mm medium gauge lacquered stainless steel pipe balustrade fitted with 6 mm thick stainless steel flats and stainless steel shoes as approved by engineer and securely fixed to RCC work. |