

Technical Specification of enquiry no. E-7130559

Sl.	Description	Qty.	Delivery
1	PROVIDING SINGLE OUTLET, FEMALE OBLIQUE TYPE HYDRANT LANDING VALVE AS PER IS 5290, TYPE-A.WITH WORKING PRESSURE 7 KG/CM2 AND TEST PRESSURE WITHIN RANGE 14 KG/CM2-21 KG/CM2, INLET CONNECTION:80 MM FLANGED DRILLED TO ASNI B 16.5. 150# FLAT FACE & OUTLET CONNECTION: INSTANTANEOUS SPRING LOCK TYPE COUPLING OF SIZE 63 MM AS PER IS: 5290 WITH CAP AND CHAIN. (MAKE NEW AGE / AAAG / SUPEREX / HD FIRE) MATERIAL OF CONSTRUCTION: A) BODY & BONNET: GUN METAL AS PER IS:318,GR. LTB-2, B) STOP VALVE, VALVE SEAT & CHECK NUT: GUN METAL AS PER IS:318, GR. LTB-2, C) VALVE SPINDLE: BRASS: 319, D) HAND WHEEL: CAST IRON TO IS:210 , E) BLANK CAP: GUN METAL AS PER IS:318, GR. LTB-2.	5 Nos.	Dec-13
2	PROVIDING JET TYPE (INSTANTANEOUS MALE COUPLING) 63 MM SHORT BRANCH PIPE WITH NOZZLE LENGTH 20 MM AS PER IS:903.SBP SHOULD HAVE WORKINGP RESSURE OF 7 KG/CM2 & TEST PRESSURE OF 21 KG/CM2. MATERIAL OF CONSTRUCT ION : BRANCH PIPE & NOZZLE : GUN METAL AS PER IS:318, GR. LTB-2. WASHER : IS:937 TYPE -B(MAKE : NEW AGE /AAAG / SUPEREX / HD FIRE)	25 Nos.	Dec-13

Note

- 1. Erection & Commissioning not required.**
- 2. EMD & CEBG is not required.**
- 3. Approval of sample is required before supply.**
- 4. Brand name should be written on the item.**
- 5. Material should be of first quality.**