

SPECIFICATION OF DMM / SOLAR HITESTER

Environment friendly hand held DMM incorporating both solar /mains charged battery operation with light meter functions.

SPECIFICATION:

| | |
|----------------------------|----------------------------------------------------|
| DC voltage ranges | : 420 mV to 600 Volts |
| Accuracy | : 1.5 % |
| AC voltage ranges | : 5 V to 600 Volts. |
| Accuracy | : 2.5 % |
| Frequency measuring ranges | : 50 to 500 Hz. |
| Continuity | : audible sound < than 50Ω |
| Light meter functions | : 50 to 50,000 Lux. |
| Range selection | : Auto / Manual |
| Power supply function. | : rechargeable lithium battery with auto power off |
| Accessories | : soft carrying case |
| | : test leads |
| | : Operating manual |

Kindly note:

1. The instrument offered can be better than the above specifications
2. Should have service facility in India with factory trained engineers to take care of the equipment supplied To reduce the down time.
3. The produce catalog should contain only the product offered in depth preferably highlighting the model Offered.
4. Two sets of product catalogue to be enclosed with the offer in original.
5. Offer without original catalog will be rejected.
6. Vendor should submit the offer with detailed specification of product offered. The offer given “ as per your specifications “ will be rejected.