

MIAINO4787

ANNEXURE-I : COOLANT PUMP SPECIFICATIONS		
Sl. No	Mat. No	Description
1	HY8310665237	Coolant Pump Size: 100/270, 0.37KW Discharge- 100 LPM, Immersion Depth-270MM, Head: 2 Mrts, 0.5 AMPS, 0.75 PF, 415 V, 3-Phase, Along with one Spare Impeller
2	HY8310667108	Coolant Pump Size: 160/220, 0.37KW 3-Phase, 415 Volts, 0.75 PF, Discharge-160 LPM, Immersion Depth -220MM, Along with one Spare Impeller
3	HY8310666993	Coolant Pump Size: 160/270, Power: 0.37KW 3-Phase, 415 Volts, 2800RPM, 0.75 PF, Discharge-160 LPM,Immersion Depth -270MM, Head: 2 Mtrs, Along with one Spare Impeller
4	HY8310667078	Coolant Pump Size: 80/220, Power: 0.18 KW 3-Phase, 415 Volts, 2800 RPM, 0.75 PF, Discharge-80 LPM,Immersion Depth -220MM, Head: 2 Mtrs, Along with one Spare Impeller
5	HY8310667051	Coolant Pump Size: 63/120, Power: 0.18 KW 3-Phase, 415 Volts, 2800RPM, 0.75 PF, Discharge-63 LPM,Immersion Depth -120 MM, Head: 2 Mtrs, Along with one Spare Impeller
6	HY8310667060	Coolant Pump Size: 63/170, Power: 0.18 KW 3-Phase, 415 Volts, 2800RPM, 0.75 PF, Discharge-63 LPM,Immersion Depth -170 MM, Head: 2 Mtrs, Along with one Spare Impeller
7	HY8310667086	Coolant Pump Size: 100/220, Power: 0.25 KW 3-Phase, 415 Volts, 2800RPM, 0.75 PF, Discharge- 100 LPM,Immersion Depth -220 MM, Head: 2 Mtrs, Along with one Spare Impeller
8	HY8310665245	Coolant Pump Size: 40/170, 0.1 KW Discharge- 40 LPM, Impression Depth-170MM, Head: 2 Mrts, 0.5 AMPS, 0.75 PF, 415 V, 3-Phase, Along with one Spare Impeller
9	HY8442276513	Vertical Multistage Immersible Self Priming Centrifugal Pump With Motor. Discharge: 3 m3/ Hr, Head : 48.9 Mtrs, Motor Rating : 1.1 KW/ 1.5 Hp Pump Inlet and Outlet End Fittings to be Supplied
10	HY8442276521	Vertical Multistage Immersible Self Priming Centrifugal Pump With Motor. Discharge: 10 m3/ Hr, Head : 97 Mtrs, Motor Rating : 4 KW/ 5.5 Hp Pump Inlet and Outlet End Fittings to be Supplied
11	HY8442276530	Horizontal Multistage Close Coupled Mono Block Centrifugal Pump, Discharge: 8 m3/ Hr, Head : 28.3 Mtrs, Motor Rating : 1.2 KW/ 1.6 Hp Pump Inlet and Outlet End Fittings to be Supplied
12	HY8442276548	Vertical Multistage Immersible Self Priming Centrifugal Pump With Motor. Discharge: 3 m3/ Hr, Head : 48.3 Mtrs, Motor Rating : 0.75 KW/ 1 HP Pump Inlet and Outlet End Fittings to be Supplied


B. KOTYA
 वरिष्ठ प्रबंधक (टिडी व जीटी) सर्विसिस
 Sr. Manager / TC & GT / Services
 फोन: ३३७४६६ / P.H.E.L. Hyd-502 032.