

PSGSG/12 -13/03	<b>Product Specifications For ALUMINIUM RODS</b>		Drg. No.	
			Date	19.02.15
			Product	<b>GSM 400</b>
<b>1.0</b>	<b>Application:</b> Aluminum rods shall be used for Gas Insulated switchgear Equipment			
<b>2.0</b>	<b>Material:</b> HE -30 Aluminum rods			
<b>3.0</b>	<b>Dimensions:</b>			
	<b>S.No</b>	<b>Diameter (D), mm</b>	<b>Length(mm)</b>	<b>Qty.</b>
	1	230 ±0.5	250±1	15
<b>4.0</b>	<b>Specifications:</b>			
	1. Electrical conductivity of material shall be greater than 45 % (IACS)			
	2. Surface finish of the components shall be at least RA 0.8.			
	3. The component shall be free from dirt, grease and loose particles.			
<b>5.0</b>	Quotation shall be submitted by supplier on <b>price per piece</b> basis only.			
<b>6.0</b>	<b>Packing:</b>			
	The components shall be packed in high density cardboard boxes, with a primary wrapped in polyethylene and packed individually in dust free boxes after degreasing. The components shall be guaranteed against all manufacturing defects.			
1/2	<b>PSGSG/12-13/03.doc</b>			<i>N. Chandrakanth</i> <b>Signature</b>