

## Technical Details of Spares for CNC machines

Sl. No.	Material Code	Quantity	Unit	Lot	Delivery Schedule
1	<b>HW8536220902</b>	5	NO	1	15/05/2015
	DC FULLY ENCLOSED POWER SUPPLY; 24V,40A REGULATION: 3% OR BETTER NOMINAL INPUT:400-500V OR MORE, 3 PHASE, 50HZ INPUT FREQUENCY RANGE:47-63 HZ OR MORE OUTPUT:ADJUSTABLE BY POTENTIOMETER OVERLOAD PROTECTION MOUNTING:SNAPS ON DIN RAIL(EN 60715 35X15MM) STATUS DISPLAY: GREEN LED FOR 24V OK.				
2	<b>HW8536220910</b>	15	NO	1	15/05/2015
	DC FULLY ENCLOSED POWER SUPPLY :24V,20A REGULATION:3% OR BETTER NOMINAL I/P: 400-500 OR MORE, 3 PHASE, 50 HZ INPUT FREQUENCY RANGE: 47-63 HZ OR MORE OUTPUT: ADJUSTABLE BY POTENTIOMETER OVERLOAD PROTECTION MOUNTING: SNAPS ON DIN RAIL (EN 60715- 35X15MM) STATUS DISPLAY:GREEN LED FOR 24V OK.				
3	<b>HW8536220929</b>	15	NO	1	15/05/2015
	DC FULLY ENCLOSED POWER SUPPLY :24V,10A REGULATION: 3% OR BETTER NOMINAL INPUT:200-230V OR MORE, 1 PHASE , 50HZ INPUT FREQUENCY RANGE: 47..63HZ OR MORE OUTPUT: ADJUSTABLE BY POTENTIOMETER O/L PROTECTION MOUNTING: SNAPS ON DIN RAIL (EN 60715-35X15MM) STATUS DISPLAY:GREEN LED FOR 24V OK.				
4	<b>HW8536220937</b>	15	NO	1	15/05/2015
	DC FULLY ENCLOSED POWER SUPPLY :24V,5A REGULATION: 3% OR BETTER NOMINAL INPUT:200-230V OR MORE, 1 PHASE,50HZ INPUT FREQUENCY RANGE:47..63HZ OR MORE OUTPUT:ADJUSTABLE BY POTENTIOMETER O/L PROTECTION MOUNTING: SNAPS ON DIN RAIL (EN 60715-35X15MM) STATUS DISPLAY: GREEN LED FOR 24V OK.				

## Technical Details of Spares for CNC machines

5	<b>HW8536221348</b>	5	NO	2	15/05/2015
DC FULLY ENCLOSED POWER SUPPLY :24V,20A,REGULATION:3% OR BETTER,NOMINAL INPUT:400..500V OR MORE,2PHASE,50HZ,INPUT FREQUENCY RANGE:47..63HZ OR MORE OUTPUT: ADJUSTABLE BY POTENTIOMETER, OVERLOAD PROTECTION,MOUNTING: SNAPS ON DIN RAIL(EN 60715-35X 15MM)STATUS DISPLAY:GREEN LED FOR 24V OK					
6	<b>HW8536221356</b>	5	NO	3	15/05/2015
DC FULLY ENCLOSED POWER SUPPLY 24V,10A,REGULATION:3% OR BETTER,NOMINAL INPUT:400..500V OR MORE,2PHASE,50HZ,INPUT FREQ RANGE:47..63HZ OR MORE OUTPUT ADJUSTABLE BY POTENTIOMETER, OVERLOAD PROTECTION,MOUNTING: SNAPS ON DIN RAIL(EN 60715-35X 15MM)STATUS DISPLAY:GREEN LED FOR 24V OK					

**Remarks:**

\*\* Warranty Certificate required for one year from the date of dispatch.

\*\* Vendor shall quote with make, model number and attach relevent catalogue with the offer.