


66  
Annexure-IV A

~~Annexure-IV~~

~~Annexure-A~~

Specification of Non-Woven Fibre Glass Chopped Strand Mat (300 gm/sq mtr.)

- Product : Non-Woven Fibre Glass chopped Strand Mat held by powder binder suitable for use with Epoxy Resin in Cast Resin Dry Type Transformer
- The Mat should have uniform density and thickness
- Width of FG mat : 1040 mm
- Filament Size : 12 micron
- Length of FG Chopping /Filament : 50 mm (Approx.)
- Grade : Electrical grade (Type-E / E-Glass)
- Weight per unit Area : 300 gm / sq. mtr.
- Tensile Strength : 140 N /sq. mm
- Sample of the Mat shall be submitted with the offer for evaluation and trial.



(ANAND SONI)  
Sr. Manager (T.R.E.)  
B.P.E.C. Jhansi

65


Amnawer - IV B

~~Amnawer - IV B~~

~~Amnawer - IV B~~

Specification of Non-Woven Fibre Glass Chopped Strand Mat (600 gm/sq mtr.)

- Product : Non-Woven Fibre Glass chopped Strand Mat held by powder binder suitable for use with Epoxy Resin in Cast Resin Dry Type Transformer
- The Mat should have uniform density and thickness
- Width of FG mat : 1040 mm
- Filament Size : 12 micron
- Length of FG Chopping /Filament : 50 mm (Approx.)
- Grade : Electrical grade (Type-E / E-Glass)
- Weight per unit Area : 600 gm / sq. mtr.
- Tensile Strength : 480 N /sq. mm
- Sample of the Mat shall be submitted with the offer for evaluation and trial.



(ANAND SONI)  
Sr. Manager (T.R.S.)  
B.H.B. Jhansi