

**JOB: Foundation work up to finished floor level (FFL) with its Electrification works for 6 Nos of closed PEB sheds (60 Mtr x 15Mtr) at 2x800 MW NTPC Ramagundam STPP, Karimnagar Telangana**

SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
<b>SECTION-A</b>					
Sec. A	1(A)	EARTH WORK EXCAVATION FROM 0 (ZERO) TO 2 M DEPTH IN ALL KINDS OF SOIL (EXCEPT SOFT ROCK AND HARD ROCK) FOR FOUNDATIONS RAMPS ETC., AS DIRECTED BY BHEL ENGINEER INCLUDING REMOVING THE EXCAVATED MATERIALS UP TO A DISTANCE OF 50M, DEWATERING (BOTH GROUND WATER AS WELL AS RAIN WATER) AND KEEP THE AREA DRY TILL COMPLETION OF ALL THE WORKS, LABOURS, MATERIALS AND REQUIRED T&Ps ETC. COMPLETE.	M3	851.00	0.926608
Sec. A	1(B)	EARTH WORK EXCAVATION FROM 0 (ZERO) TO 2 M DEPTH FOR SOFT ROCK AND HARD ROCK (BY MANUAL CHISELING OR BY MECHANICAL MEANS BUT WITHOUT BLASTING) FOR FOUNDATIONS, RAMP ETC., AS DIRECTED BY BHEL ENGINEER INCLUDING REMOVING THE EXCAVATED MATERIALS UP TO A DISTANCE OF 50M, DEWATERING (BOTH GROUND WATER AS WELL AS RAIN WATER) AND KEEP THE AREA DRY TILL COMPLETION OF ALL THE WORKS, LABOURS, MATERIALS AND REQUIRED T&Ps ETC. COMPLETE.	M3	107.00	0.188833
Sec. A	1(C)	EARTH WORK EXCAVATION FROM 2.0M TO 4.0 M DEPTH IN ALL KINDS OF SOIL (EXCEPT HARD ROCK AND SOFT ROCK) FOR FOUNDATIONS, RAMPS ETC., AS DIRECTED BY BHEL ENGINEER INCLUDING REMOVING THE EXCAVATED MATERIALS UP TO A DISTANCE OF 50M, DEWATERING (BOTH GROUND WATER AS WELL AS RAIN WATER) AND KEEP THE AREA DRY TILL COMPLETION OF ALL THE WORKS, LABOURS, MATERIALS AND REQUIRED T&Ps ETC. COMPLETE.	M3	54.00	0.078891
Sec. A	1(D)	EXCAVATION IN ALL KINDS OF SOIL INCLUDING SOFT & HARD ROCK ((BY MANUAL CHISELING OR BY MECHANICAL MEANS BUT WITHOUT BLASTING) FROM 2 TO 4M DEPTH FOR SEPTIC TANK AND SOAK PIT, WHEREVER REQUIRED INCLUDING REMOVING THE EXCAVATED MATERIALS UP TO A DISTANCE OF 50M, DEWATERING (BOTH GROUND WATER AS WELL AS RAIN WATER) AND KEEP THE AREA DRY TILL COMPLETION OF ALL THE WORKS, LABOURS, MATERIALS AND REQUIRED T&Ps ETC. COMPLETE.	M3	54.00	0.202780
Sec. A	1(E)	SUB GRADE PREPARATION: CUTTING LEVELLING, FILLING WITH EXCAVATED EARTH, WATERING AND CONSOLIDATION FOR SHED AND PLINTH PROTECTION AREA BEFORE LAYING THE PCC WITH ALL T&P, LABOURS, MATERIALS ETC. COMPLETE.	M2	6804.00	3.469199
Sec. A	1(F)	EARTH WORK IN EXCAVATION IN HARD ROCK REQUIRING CONTROLLED BLASTING INCLUDING WEDGING, LINE DRILLING, PRE SHEARING ETC AS REQUIRED, SETTING OUT, LEVELLING, DEWATERING (WHEREVER REQUIRED), SHORING & STRUTTING (WHEREVER REQUIRED), DRESSING THE SIDES & BOTTOM, ALL LIFTS, NECESSARY LICENSES/STATUATORY CLEARANCES FOR BLASTING, SUPPLY, STORAGE & HANDLING OF BLASTING MATERIALS, STACKING/DISPOSAL OF SURPLUS EXCAVATED MATERIAL , SPREADING / LEVELLING OF DISPOSED MATERIALS ETC ALL COMPLETE FOR FOLLOWING DEPTHS BELOW GROUND LEVEL.			0.000000
Sec. A	1(F) (i)	Depth from ground level but not exceeding 2 m	CUM	10.00	0.034100
Sec. A	1(F) (ii)	Depth exceeding 2 m but not exceeding 4 m	CUM	10.00	0.034100
Sec. A	1(F) (iii)	Depth exceeding 4 m but not exceeding 6 m	CUM	5.00	0.022908

SEAL AND SIGN OF BIDDER

**JOB: Foundation work up to finished floor level (FFL) with its Electrification works for 6 Nos of closed PEB sheds (60 Mtr x 15Mtr) at 2x800 MW NTPC Ramagundam STPP, Karimnagar Telangana**

SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
Sec. A	2	<b>DISPOSAL</b> OF EXCAVATED EARTH/ROCK (NOT SUITABLE FOR BACK FILLING) BEYOND INITIAL LEAD OF 50M AND UPTO A MAXIMUM LEAD OF 2 KM OR PART THEREOF INCLUDING LOADING, UNLOADING , TRANSPORTING AND SPREADING AS PER DIRECTION OF BHEL ENGINEER .	M3	475.00	0.371452
Sec. A	3	<b>BACKFILLING</b> OF FOUNDATION ,FLOORS AND PLINTH IN LAYERS NOT EXCEEDING 150MM THICK. INCLUDING WATERING AND CONSOLIDATING ETC. COMPLETE AS PER STANDARD SPECIFICATION AND INSTRUCTED BY BHEL ENGINEER.			0.000000
Sec. A	A	WITH <b>GOOD EXCAVATED SOIL</b> AVAILABLE FROM THE EARTH WORK.	M3	534.00	0.372515
Sec. A	B	WITH <b>GOOD</b> EARTH BROUGHT FROM OUTSIDE FROM CONTRACTOR'S OWN SOURCE INCLUDING ROYALTY ETC.	M3	1305.00	3.742472
Sec. A	C	WITH <b>GRANULAR MURUM</b> IN LAYERS (THICKNESS OF EACH LAYER SHOULD NOT EXCEED 150MM ) BELOW FOUNDATIONS, AND RAMP AS PER STANDARD SPECIFICATION, RELEVANT DRAWINGS AND INSTRUCTED BY BHEL ENGINEER INCLUDING ROYALTY. CONTRACTOR HAS TO SUBMIT ROYALTY CERTIFICATE FROM CONCERNED STATE GOVT. MINING DEPARTMENT	M3	143.00	0.843104
Sec. A	D	PROVIDING <b>STONE SOLING</b> OF REUIRED THICKNESS AS PER DRAWING BELOW FLOORING, RAMP, COLUMN FOUNDATIONS OF STORAGE SHED ETC. BY USING 80 MM SIZE HARD BROKEN BLACK GRANITE/ QUARTIZITE/ GNEISS/ TRAP STONE METAL INCLUDING GRANULAR MURRUM PACKING, WATERING & COMPACTION ETC COMPLETE.AS PER STANDARD SPECIFICATION AND INSTRUCTED BY BHEL ENGINEER	M3	1450.00	15.020827
Sec. A	4(A)	PROVIDING AND LAYING OF <b>PLAIN CEMENT CONCRETE OF MIX 1:4:8</b> USING OPC GRADE 43/53, 20 MM DOWN SIZE HARD BROKEN GRANITE STONE JELLY FOR <b>FOUNDATION, RAMPS</b> AND WHEREVER REQUIRED INCLUDING SHUTTERING, FINISHING, CURING, CONSOLIDATION ETC. COMPLETE AS PER STANDARD SPECIFICATIONS AND AS DIRECTED BY BHEL ENGINEER.	M3	74.00	2.316335
Sec. A	4(B)	PROVIDING AND LAYING OF <b>100 MM THICK PLAIN CEMENT CONCRETE OF MIX 1:3:6</b> USING OPC GRADE 43/53, 20 MM DOWN SIZE HARD BROKEN GRANITE STONE JELLY WITH TROWEL FINISH FOR <b>PLINTH PROTECTION AND WHEREVER REQUIRED</b> INCLUDING SHUTTERING, FINISHING, CURING, CONSOLIDATION ETC. COMPLETE AS PER STANDARD SPECIFICATIONS AND AS DIRECTED BY BHEL ENGINEER.	M3	72.00	2.511878
Sec. A	4(C)	PROVIDING AND LAYING OF <b>100 MM THICK PLANE CEMENT CONCRETE OF MIX 1:2:4</b> USING OPC GRADE 43/53, 20MM DOWN SIZE HARD BROKEN GRANITE STONE JELLY WITH TROWEL FINISH FOR <b>FLOOR, RAMPS WHEREVER REQUIRED</b> INCLUDING MECHANICAL MIXING, VIBRATION, CURING, FORM WORK & CENTERING AS PER DRAWING AND SPECIFICATION AND DIRECTED BY BHEL ENGINEER BUT EXCLUDING COST OF REINFORCEMENTS.	M3	574.00	22.366847
Sec. A	4(D)	PROVIDING AND LAYING OF <b>RCC MIX 1:1.5:3</b> USING OPC GRADE 43/53, 20MM DOWN SIZE HARD BROKEN GRANITE STONE 20MM DOWN SIZE HARD BROKEN GRANITE STONE JELLY WITH TROWEL FINISH FOR <b>FOUNDATION ,RAFT COLOUM,PLINTH BEAM</b> AND WHEREVER REQUIRED INCLUDING MECHANICAL MIXING, VIBRATION, CURING, FORM WORK & CENTERING AS PER DRAWING AND SPECIFICATION AND DIRECTED BY BHEL ENGINEER BUT EXCLUDING COST OF REINFORCEMENTS.	M3	372.00	17.256622

SEAL AND SIGN OF BIDDER

**JOB: Foundation work up to finished floor level (FFL) with its Electrification works for 6 Nos of closed PEB sheds (60 Mtr x 15Mtr) at 2x800 MW NTPC Ramagundam STPP, Karimnagar Telangana**

SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
Sec. A	5	PROVIDING AND LAYING <b>DPC</b> (DAMP PROOF COURSE) 50MM THICK IN 1:2:4 CEMENT CONCRETE LAYER USING OPC GRADE 43/53 AND WITH 6MM DOWN AGGREGATE, INCLUDING FORMWRK, BITUMEN FELT USING CEMENT WITH WATER PROOFING COMPOUND ETC. COMPLETE	M2	212.00	0.536851
Sec. A	6	PROVIDING , CUTTING, BENDING AND FIXING IN POSITION <b>REINFORCEMENT OF VARIOUS DIA. USING HIGH TENSILE TOR STEEL (Fe - 415/500 ) FOR FOUNDATIONS, COLUMNS, BEAMS WHEREVER REQUIRED</b> AS PER DRAWING AND SPECIFICATION AND AS DIRECTED BY BHEL ENGINEER INCLUDING COST OF ALL MATERIALS, LEADS, LIFT, LABOURS, MS BINDING WIRE 18/20 GAUGE, TACK WELDING AND SUPPORTING IF REQUIRED COMPLETE.	MT	24.00	12.436823
Sec. A	7 (A)	PROVIDING <b>BRICK WORK IN CM 1:6</b> (1 CEMENT & 6 COARSE SAND) USING OPC GRADE 43/53 AND <b>LOCALLY AVAILABLE BURNT CLAY BRICKS</b> (MIN STRENGTH 35 KG/CM <sup>2</sup> ) AS PER DRAWING AND SPECIFICATION FOR FOUNDATION, SUPER STRUCTURE ETC. INCLUDING COST OF ALL MATERIALS, LABOUR, SCAFFOLDING, CURING , AT ALL ELEVATIONS AND LEVELS , RAKING OUT JOINTS ETC. COMPLETE AND AS DIRECTED BY ENGINEER . EXCLUDING PLASTERING & PAINTING.	M3	39.00	1.258415
Sec. A	7(B)	PROVIDING <b>BRICK WORK IN CM 1:6</b> (1 CEMENT & 6 COARSE SAND) USING OPC GRADE 43/53 AND <b>FLY ASH LIME BRICKS</b> (FAL - MIN STRENGTH 35 KG/CM <sup>2</sup> ) AS PER DRAWING AND SPECIFICATION FOR FOUNDATION, WALL ETC. INCLUDING COST OF ALL MATERIALS, LABOUR, SCAFFOLDING, CURING, AT ALL ELEVATIONS AND LEVELS , RAKING OUT JOINTS ETC. COMPLETE AND AS DIRECTED BY ENGINEER. EXCLUDING PLASTERING & PAINTING.	M3	155.00	5.133457
Sec. A	8	PROVIDING <b>2MM THICK NEAT CEMENT FINISH USING OPC GRADE 43/53</b> OVER CONCRETE BASE FOR FLOORING, PAVING, PLASTERED SURFACE ETC. INCLUDING CURING & CLEANING AND SCAFFOLDING COMPLETE.	M2	5508.00	1.425979
Sec. A	9	PROVIDING <b>PLASTERING WITH CEMENT MORTAR -1:6 (1 CEMENT &amp; 6 FINE SAND) USING OPC GRADE 43/53</b> OVER BOTH INTERNAL AND EXTERNAL FACES OF BRICKWORK AND CONCRETE SURFACES ETC. AT ALL LEVELS INCLUDING PREPARING THE SURFACE, RAKING JOINTS, SCAFFOLDING, CURING, COST OF ALL MATERIALS, LABOUR ETC. COMPLETE.			0.000000
Sec. A	A	EXTERNAL PLASTERING - 20 MM THICK	M2	524.00	0.739366
Sec. A	B	INTERNAL PLASTERING -12MM THICK	M2	276.00	0.258476
Sec. A	10	PROVIDING & APPLYING <b>COLOUR WASH -THREE COATS</b> ON NEWLY PLASTERED EXTERNAL SURFACE OF SHED BY USING BEST <b>SHALE LIME</b> TO GIVE AN EVEN SHADE INCLUDING PREPARING THE SURFACE LIKE CLEANING AND BRUSHING & BROOMING OF WALLS AND IN ACCORDANCE WITH STANDARD SPECIFICATION. RATE INCLUDE COST OF ALL MATERIALS , COLOURING AGENT, BASE COAT OF WHITE WASH, APPROVED ADDESSIVE, SCAFFOLDING AT ALL LEVEL, BRUSH ETC. COMPLETE.	M2	539.00	0.072463
Sec. A	11	<b>PROVIDING &amp; APPLYING WHITE WASH - THREE COATS</b> ON NEWLY PLASTERED INTERNAL SURFACE OF SHED BY USING BEST SHALL LIME TO GIVE AN EVEN SHADE INCLUDING PREPARING THE SURFACE LIKE CLEANING AND BRUSHING & BROOMING OF WALLS AND IN ACCORDANCE WITH STANDARD SPECIFICATION. RATE INCLUDE COST OF ALL MATERIALS , COLOURING AGENT, APPROVED ADDESSIVE, SCAFFOLDING AT ALL LEVEL, BRUSH ETC. COMPLETE.	M2	288.00	0.037999

SEAL AND SIGN OF BIDDER

**JOB: Foundation work up to finished floor level (FFL) with its Electrification works for 6 Nos of closed PEB sheds (60 Mtr x 15Mtr) at 2x800 MW NTPC Ramagundam STPP, Karimnagar Telangana**

SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
Sec. A	12	SUPPLYING & FIXING IN POSITION <b>MS FOUNDATION BOLTS</b> WITH HEXAGONAL NUTS (3 NOS. NUTS WITH EACH BOLT) IN RCC COLUMNS OF PEB SHED FOUNDATION AS PER DRAWINGS & DIRECTION OF BHEL ENGINEER	MT	4.00	2.556154
		<b>TOTAL VALUE OF SECTION-A IN Rs.</b>			94.215454
<b>SECTION B</b>					
<b>NAME OF THE WORK : INTERNAL ELECTRIFICATION WORK OF 6 No. SHED (60MX15M) AT 2x800MW NTPC KARIMNAGAR TELANGANA STPP</b>					
SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
Sec.B	1	SUPPLYING & INSTALLING <b>POWER DISTRIBUTION BOARD</b> COMPLETE WITH: COMMON BOARD FOR ALL SHEDS. 1) INCOMING MCB TPH 100 AMPS. - 1 NO. 2) OUTGOING MCB TPH 32 AMPS. -3NOS. 3) RCCB DP 25/20 AMPS. - 2NOS. 4) OUTGOING MCB SP 6 AMPS - 6NOS. All RCCBs, MCBs SHALL BE MDS/INDO KOPP MAKE. DISTRIBUTION BOARDS SHALL BE SIEMENS / MDS / INDO KOPP MAKE WITH INTERNAL BUSBARS, INTERNAL WIRING, 2 NOS. EARTHING TERMINALS, EARTH CONNECTIONS, INCLUDING GLANDS, LUGS.	Set	1.00	0.103198
Sec.B	2	SUPPLYING & FIXING <b>WALL MOUNTING TYPE LIGHTING PANELS</b> , EACH WITH : (1) INCOMING MCB TPN -32 AMPS - 1NO. (2) RCCB DP 32 AMPS - 2NOS (3) MCB SP 6AMPS - 30 NOS.. All RCCBs, MCBs SHALL BE MDS/INDO KOPP MAKE. LIGHTING PANEL SHALL BE <b>SIEMENS/MDS/INDO KOPP</b> MAKE WITH INTERNAL BUSBARS, 2 NOS. EARTHING TERMINALS, EARTH CONNECTIONS, INCLUDING GLANDS, LUGS & WIRING FROM MAIN DB	Set	6.00	0.619189
Sec.B	3	PROVIDING AND INSTALLING <b>WIRING USING 2.5 SQ.MM</b> COPPER CONDUCTOR THROUGH PVC CONDUIT OF REQUIRED SIZE WITH ACCESSORIES AND FIXTURES .WIRING SHALL BE CONCEALED TYPE FOR COMPUTER ROOM, OFFICE SHED & FOR REST OF SHEDS OPEN AND WHREVER REQUIRED IN PVC CONDUIT OF REQUIRED SIZE.	PER POINT	284.00	0.292447
Sec.B	4	PROVIDING AND INSTALLING <b>WIRING FOR USING 4.0 SQ.MM</b> COPPER CONDUCTOR THROUGH PVC CONDUIT OF REQUIRED SIZE WITH ACCESSORIES AND FIXTURES .WIRING SHALL BE CONCEALED TYPE FOR COMPUTER ROMM, OFFICE SHED & FOR REST OF SHEDS OPEN AND WHREVER REQUIRED IN PVC CONDUIT OF REQUIRED SIZE.	PER POINT	18.00	0.041771

SEAL AND SIGN OF BIDDER

**JOB: Foundation work up to finished floor level (FFL) with its Electrification works for 6 Nos of closed PEB sheds (60 Mtr x 15Mtr) at 2x800 MW NTPC Ramagundam STPP, Karimnagar Telangana**

SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
Sec.B	5	PROVIDING AND INSTALLING <b>WIRING FOR MAINS USING 6.00 SQ.MM</b> COPPER CONDUCTOR OF ISI MAKE. USING CONCEALED TYPE WIRING/PVC CONDUIT OF REQUIRED SIZE.	PER POINT	18.00	0.041771
Sec.B	6	PROVIDING AND INSTALLING <b>WIRING FOR MAINS USING 16.00 SQ.MM</b> COPPER CONDUCTOR OR ISI MAKE USING CONCEALED TYPE WIRING/PVC CONDUIT OF REQUIRED SIZE.	PER POINT	18.00	0.074275
Sec.B	7	PROVIDING AND INSTALLATION OF <b>PLUG POINT OF 5A SOCKET</b> (ANCHOR OR EQUIV.) OUTLET INCLUDING WIRING TERMINATION. THIS INCLUDES TUBE LIGHT FITTINGS ETC. COMPLETE.	NO	18.00	0.074275
Sec.B	8	PROVIDING AND INSTALLATION OF <b>PLUG POINT OF 15A SOCKET</b> (ANCHOR OR EQUIV.) OUTLET INCLUDING WIRING TERMINATION. THIS INCLUDES TUBE LIGHT FITTINGS V	NO	18.00	0.167221
Sec.B	9	PROVIDING AND FIXING <b>ORDINARY TUBELIGHT WITH FRAME</b> OF STANDARD MANUFACTURER LIKE PHILIPS/BAJAJ OR EQUIVALENT AS APPROVED BY BHEL. THIS INCLUDES TUBE LIGHT FITTINGS ETC. COMPLETE.	NO.	170.00	0.394511
Sec B	10	PROVIDING AND FIXING CEILING FAN 48" DIAMETER OF APPROVED COMPANY SUCH AS CROMPTON GREEVES OR ANY OTHER STANDARD MANUFACTURER AS DIRECTED BY BHEL THIS INCLUDES ALL ACCESSORIES REQUIRED TO COMPLETE THE WORK OF FAN INSTALLATION.	NO	6.00	0.060351
Sec.B	11	PROVIDING AND FIXING <b>CALLING BELLS</b> (WITH INDICATOR LIGHT)	NO	1.00	0.001029
Sec.B	12	PROVIDING <b>EARTHING PITS WITH 2 " DIA</b> , 2 M LONG GI PIPES WITH FLANGE & GI WIRES WITH CHARCOAL, SALT AND AS PER THE STANDARD PRACTICE FOR ELECTRICAL CONNECTION.RATE SHALL BE INCLUSIVE OF ALL MATERIALS, LABOURS, ETC COMPLETE.	NO	3.00	0.046450
Sec.B	13	PROVIDING & FIXING <b>ALUMINIUM DISPERSIVE LUMINAIRE</b> ENAMELED GREEN AND WHITE WITH CAST ALUMINIUM FLANGE AND NIPPLE SUITABLE FOR USE WITH GLS LAMP, DOME 12" DIAMETER, WITH HANGING BRACKET AND <b>200W GLS LAMP</b> OF CROMPTON OR EQUIVALENT <b>BAJAJ/PHILIPS</b> MAKE, COMPLETE.	Nos.	108.00	0.668886
Sec.B	14	<b>WIRING WITH 2.5 SQ MM</b> ISI MARK COPPER WIRE FOR ABOVE IN PVC CONDUIT ALONG WITH GI EARTH WIRE INCLUSIVE OF ALL MATERIAL, LABOUR ETC. COMPLETE	Per Point	18.00	0.278702
Sec.B	15	SUPPLY OF <b>CABLES 2 CORE X 10 SQMM ALUMINIUM ARMoured</b> PVC INSULATED CABLE CONFIRMING TO IS 1554 ( PART -I)	RM	300.00	0.199233
Sec.B	16	INSTALLATION OF <b>CABLES 2 CORE X 10 SQMM ALUMINIUM ARMoured</b> PVC INSULATED CABLE CONFIRMING TO IS 1554 ( PART -I) INCLUDING LAYING OF CABLE BELOW GROUND , EXCAVATION OF TRENCH OF 600 MM DEPTH IN ALL KIND OF SOIL, TERMINATION OF CABLES CORES WITH CRIMP TYPE LUGGS, PROVIDING SAND LAYER BELOW/ ABOVE THE CABLE, BRICK LAYING BOTH SIDE /ABOVE THE ABOVE THE CABLE AND BACK FILLING ETC COMPLETE. CABLES ARE TO BE LAID FROM 415 VOLT AC POWER FEEDER PILLAR BOARD BOARD TO LIGHTING POLES & POLE TO POLE	RM	300.00	0.091781

SEAL AND SIGN OF BIDDER

**JOB: Foundation work up to finished floor level (FFL) with its Electrification works for 6 Nos of closed PEB sheds (60 Mtr x 15Mtr) at 2x800 MW NTPC Ramagundam STPP, Karimnagar Telangana**

SEC.	SL.NO	DESCRIPTION OF WORK	UNIT	QTY.	Weightage %
Sec.B	17	SUPPLY OF CABLES 3 -1/2 COREX 35 SQMM ALUMINIUM ARMoured PVC INSULATED CABLE (THREE AND HALF CORE) CONFIRMING TO IS 1554 ( PART -I)	RM	180.00	0.417718
Sec.B	18	INSTALLATION OF CABLES 3 -1/2 COREX 35 SQMM ALUMINIUM ARMoured PVC INSULATED CABLE CONFIRMING TO IS 1554 ( PART -I) INCLUDING LAYING OF CABLE BELOW GROUND , EXCAVATION OF TRENCH OF 600 MM DEPTH IN ALL KIND OF SOIL, TERMINATION OF CABLES CORES WITH CRIMP TYPE LUGGS, PROVIDING SAND LAYER BELOW/ ABOVE THE CABLE, BRICK LAYING BOTH SIDE /ABOVE THE ABOVE THE CABLE AND BACK FILLING ETC. CABLES ARE TO BE LAID FROM TRANSFORMER SUB STATION TO 415 VOLT AC DISTRIBUTION BOARD	RM	180.00	0.055068
Sec.B	19	SUPPLY OF CABLES 3 -1/2 CORE X 95 SQMM ALUMINIUM ARMoured PVC INSULATED CABLE (THREE AND HALF CORE) CONFIRMING TO IS 1554 ( PART -I)	RM	120.00	0.680526
Sec.B	20	INSTALLATION OF CABLES 3 -1/2 CORE X 95 SQMM ALUMINIUM ARMoured PVC INSULATED CABLE CONFIRMING TO IS 1554 ( PART -I) INCLUDING LAYING OF CABLE BELOW GROUND, EXCAVATION OF TRENCH OF 600 MM DEPTH IN ALL KIND OF SOIL, TERMINATION OF CABLES CORES WITH CRIMP TYPE LUGGS, PROVIDING SAND LAYER BELOW/ ABOVE THE CABLE, BRICK LAYING BOTH SIDE /ABOVE THE ABOVE THE CABLE AND BACK FILLING ETC COMPLETE. CABLES ARE TO BE LAID FROM 415 VOLT AC DISTRIBUTION BOARD TO FEEDER PILLAR BOARD , FEEDER PILLAR BOARD TO LIGHTING MAST / TOWER.	RM	120.00	0.036712
Sec.B	21	SUPPLY OF CABLES 3 -1/2 COREX 185 SQMM ALUMINIUM ARMoured PVC INSULATED CABLE (THREE AND HALF CORE) CONFIRMING TO IS 1554 ( PART -I)	RM	150.00	1.393512
Sec.B	22	INSTALLATION OF CABLES 3 -1/2 COREX 185 SQMM ALUMINIUM ARMoured PVC INSULATED CABLE CONFIRMING TO IS 1554 ( PART -I) INCLUDING LAYING OF CABLE BELOW GROUND , EXCAVATION OF TRENCH OF 600 MM DEPTH IN ALL KIND OF SOIL, TERMINATION OF CABLES CORES WITH CRIMP TYPE LUGGS, PROVIDING SAND LAYER BELOW/ ABOVE THE CABLE, BRICK LAYING BOTH SIDE /ABOVE THE ABOVE THE CABLE AND BACK FILLING ETC. CABLES ARE TO BE LAID FROM TRANSFORMER SUB STATION TO 415 VOLT AC DISTRIBUTION BOARD.	RM	150.00	0.045920
		<b>TOTAL VALUE OF SECTION B IN Rs.</b>			5.784546
		<b>TOTAL SUMMARY</b>	<b>AMOUNT</b>	<b>Weightage Percentage</b>	
		<b>Total of Section A - CONSTRUCTION WORK (FOUNDATION TO FFL) OF 6 No. SHED</b>	<b>0 00 00 000</b>	<b>94.21545400</b>	
		<b>Total of Section B- INTERNAL AND EXTERNAL ELECTRIFICATION FOR THE ABOVE</b>	<b>00 00 000</b>	<b>5.7845460</b>	
		<b>GRAND TOTAL (A+B) IN Rs.</b>	<b>0 00 00 000</b>	<b>100.000000000000</b>	

SEAL AND SIGN OF BIDDER